

Technical datasheet

Pump Unit "OTS.2-70.CIRK.SS316"

Introduction

Apart from in-line filters in hydraulic- and lube oil systems it is an advantage to initiate further care of the hydraulic and lube oil through an external filter unit, for instance off-line filtering of oil reservoirs.

For industrial use the unit is excellent for circulating different fluids in all kinds of process systems such as, but not limited, pipe- & tank systems, heat exchangers, coolers (plate & tube bundles) etc.

The unit is driven by a 380V, 0,75 kW, 16 A electrical motor, fitted to a 60 l/min stainless SS316 steel vertical centrifugal pump.

OTS item number.: 9000-366



Features

- Visual pressure indicator
- Independent of site services
- Articulated wheels mounted for site mobility

Capacity & performance

| | |
|------------------|----------------------|
| 0-2 bar pressure | Flow rate 60 l./min. |
| 3 bar pressure | Flow rate 50 l./min. |
| 4 bar pressure | Flow rate 40 l./min. |
| 5 bar pressure | Flow rate 25 l./min |

Safety features

- Gauge for pressure control
- Stainless SS316 steel drip trays fitted as standard
- Skid mounted and framed in stainless SS316 steel

Weight & dimensions

| | |
|--------------|--------|
| Length | 600 mm |
| Width | 400 mm |
| Height | 750 mm |
| Gross weight | 50 kg |