

Technical datasheet

Chemical Pump Unit "OTS.45-4.CIRK.SS316"

Introduction

The unit is driven by a 380V, 15 kW electrical motor, fitted to a 900 l/min stainless SS316 steel vertical centrifugal pump.

The high pressure series is a multi-purpose pump range suitable for a variety of different applications demanding reliable and cost efficient supply.

The unit is capable of operating with pipe dimensions from 1.5" and upwards, and can handle a variety of liquids from potable water to industrial liquids within a very wide temperature, flow and pressure scale.

For industrial use the unit is excellent for circulating different fluids in all kinds of process systems such as, but not limited to, pipe- & tank systems, heat exchangers, coolers (plate & tubebundles) etc.

The (special) design ensures a wide pressure range. It is fitted with a high pressure shaft seal suitable for the most common high pressure applications.



Features

- Skid mounted and framed in stainless SS316 steel
- Various pressure and flow options
- Suction strainer
- Forklift facility

Capacity & performance

0-6 bar pressure	Flow rate 900 l/min
7 bar pressure	Flow rate 800 l/min
8 bar pressure	Flow rate 675 l/min
9 bar pressure	Flow rate 550 l/min
10 bar pressure	Flow rate 300 l/min

Safety features

- Water resistant documentation box
- Gauge for pressure control
- Stainless SS316 steel drip trays fitted as standard

Weight & dimensions

Length	1115 mm
Width	880 mm
Height	1600 mm
Gross weight	400 kg